

Vredo Overseeders

DZ Turf-Fix





Would you like a healthy new sward?

Easily fixed with the Vredo Turf-Fix. With its famous double disc principle, Vredo can call itself the overseeding specialist in agricultural as well in the sports turf and golf markets. Next to perfect seeding, the Vredo Turf-Fix also aerates and sands the surface. These specialist processes can now be carried out at the same time by field managers, greenkeepers and gardeners using the Turf-Fix. The base unit has a width of 81 centimetres and can get into the most difficult to reach areas of a course, pitch of field. The Vredo Turf-Fix can be delivered as 3-point mounted model as well as a towed model for a 2-axle vehicle (e.g. lawn mower) or a 1-axle vehicle (e.g. Agria, BCS, Ferrari) unit. Using the red base frame, the Turf-Seed, Turf-Air or Turf-Sand can be mounted in a blink of an eye.



Overseeding with Turf-Seed

Overseeding is important aspect of keeping a lawn healthy. Young grasses will keep their colour better and will be strong enough to fight off weeds and moss. The Turf-Seed makes a small slit in the turf every 3,5 centimetres, and places the seed into the slits. The Turf-Fix's tires then close the slit through pressure, enabling a good contact between seed and soil, making the seed germinate and take root fast.

Aeration with Turf-Air

Aeration is necessary to get water, air and light into the root zone as these are the essential ingredients for an even and dark green turf. The Vredo Turf-Fix with Air Unit is equipped with solid tines and creates small holes in the lawn with a depth of approximately 3 centimetres - 260 Holes per m2. This lets the lawn breathe, strongly enhancing grass growth.





Vredo





Sanding with Turf-Sand

Sanding is necessary in order to fill the holes created by the Turf-Air. Doing this allows the breathing effect to remain for a long period of time, and the vertical holes provide optimal drainage in the root zone. The Turf-Sand can be easily attached to the Turf-Fix's mainframe. The Turf-Sand has a capacity of 114 litres. The dosing system is seamless variable and can be used with the double disc system to bring the sand approximately 2 centimetres into the soil, or without discs to dress the sand on top of the surface.



Standard new features



Spindle

Used to adjust the quantity of seed released by the machine. With the use of the seed chart at the inner side of the lid, this is an easy job.



Round lid and new striping

The latest Vredo Turf-Fix has a round lid and new striping for a real Vredo look!

Specifications **Vredo** DZ Turf - Fix Seed/Air/Sand

Туре	Working width	Row/ hole distance	Contents seed hopper	Dimensions (m)	Weight
DZ206.03.5 Seed	0,63 m.	3.5 cm	60 I.	0,82 X 0,82 X 0,80 m	230 kg
DZ206.03.5T Seed	0,63 m.	3.5 cm	60 I.	1.30 X 0,82 X 0,80 m	250 kg
DZ206.03.5T Seed (for 1-axle machine)	0,63 m.	3.5 cm	60 I.	1,24 X 0,82 X 0,80 m	260 kg
DZ206.03.5 Air	0,63 m.	6 cm hole	nvt.	0,84 X 0,81 X 0,70 m	175 kg
DZ206.03.5T Air	0,63 m.	6 cm hole	nvt.	1.43 X 0,81 X 0,70 m	195 kg
DZ206.03.5T Air (for 1-axle machine)	0,63 m.	6 cm hole	nvt.	1,24 X 0,81 X 0,70 m	205 kg
DZ206.03.5 Sand	0,63 m.	3.5 cm	114 I.	0,84 X 0,81 X 0,89 m	235 kg.
DZ206.03.5T Sand	0,63 m.	3.5 cm	114 I.	1.43 X 0,81 X 0,89 m	255 kg.
DZ206.03.5T Sand (for 1-axle machine)	0,63 m.	3.5 cm	114 l.	1,24 X 0,81 X 0,89 m	265 kg.

www.vredo.com +31 (0) 488 411 254 sales@vredo.com

Dealer:

